

MISCELLANEOUS DEVICES

Weather Station Compact WSC11

Part number: 4.9056.10.000

The interface for the instrument is digital, and consists of an RS485 interface. Together with the ID-based communication the interface facilitates the operation of the weather station in a bus.

The instrument has a GPS receiver. It serves for the determination of position and time. The sun position is calculated herefrom additionally.

The following parameters can be measured:

- Wind speed
- Wind direction
- Brightness (in North, East, South, West)
- Twilight
- Global radiation
- Precipitation
- Temperature
- Relative air humidity
- Air pressure
- Time / date
- Geostationary data
- Longitude
- Latitude
- Sun position
- Elevation
- Azimuth



Specification

Part number: 4.9056.10.000

Wind speed	
Measuring range	0 ... 40 m/s
Resolution	±5% of meas. range
Wind direction	
Measuring range	0 ... 360 °
Accuracy	±10 °
Precipitation	
Measuring range	1 / 0 (yes / no)
Temperature	
Measuring range	-30 ... +60 °C
Accuracy	±1 K @ -5 ... 25 °C (WS > 2 m/s)
Rel. Humidity	
Measuring range	0 ... 100 % rel. h.
Accuracy	±5 % rel. h. (@ 0 ... 20 °C)
Brightness	
Measuring range	0 ... 150 kLux
Accuracy	±3 % of meas. range

Twilight

Measuring range	0 ... 500 Lux
Accuracy	±10 % of meas. range

Radiation

Measuring range	0 ... 1300 W/m ²
Accuracy	±10 % of meas. range

Air pressure

Measuring range	300 ... 1100 hPa
Accuracy	±0.5 hPa @ 20 °C

Data output digital

Interface	RS485 (half duplex)
Baudrate	1200 ... 115200 Baud
Protocol	ASCII (preselected)

Operating voltage

Electronic	18 ... 30 V DC or 18 ... 28 V AC 50 / 60 Hz
Current consumption	120mA @ 24 V (max. 1,5A AC, max 0,5A DC)

General

Time synchronization	GPS
Ambient temp.	-30 ... +60 °C
Electr. connection	7 pol. Stecker
Mounting	on mast tube Ø 25mm [∧]
Dimension	Ø 130 x 70 mm
Weight	0.2 kg

Versions


As per 4.9056.10.000, but:

Product number 4.9056.10.001

Data output digital

Protocol	MODBUS RTU (preselected)
----------	----------------------------

Accessories

Product	Product name	Brief description
	Mounting angle 509564	Serves for the lateral mounting of the Weather Station COMPACT WSC11 at a vertical surface.
		General
		Material
		stainless steel 1.4301
		Dimension
		250 x 42 mm

	Cable for WSC11 510023	Assembled 7-pole connecting cable for Weather Station COMPACT WSC11 Equipment: <ul style="list-style-type: none"> • cable socket, instrument-site • open ends, receive-site • shielded • length: 5 m • with Silicon spout <hr/> General <hr/> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 70%;">Cable length</td> <td style="width: 30%;">5 m</td> </tr> </table> <hr/>	Cable length	5 m
Cable length	5 m			
	Cable for WSC11 510024	Assembled 7-pole connecting cable for Weather Station COMPACT WSC11 Equipment: <ul style="list-style-type: none"> • cable socket, instrument-site • open ends, receive-site • shielded • length: 10 m • with Silicon spout <hr/> General <hr/> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 70%;">Cable length</td> <td style="width: 30%;">10 m</td> </tr> </table> <hr/>	Cable length	10 m
Cable length	10 m			

